

Charley's GREENHOUSE & GARDEN

(800) 322-4707

charleysgreenhouse.com

#W5423 CMP Chlorgon Water Filter

MODEL HO2-WH

OWNER'S INSTRUCTIONS

INSTALLATION:

Attach the Chlorgon Water Filter to the hose bib by screwing filter clockwise onto faucet.

MAINTENANCE:

The Chlorgon Water Filter can be easily maintained by periodically performing the following:

1. Open the filter housing by unscrewing the two Filter Halves counter-clockwise.
2. Remove and reverse the direction of the Chlorgon Cartridge. Check that the O-Ring located inside each of the Filter Housing Halves is properly seated on the O-Ring Channel. *(NOTE: A small amount of Vaseline applied in the O-Ring Channel will hold the O-Ring in place.)*
3. Close the filter housing by screwing the Filter Halves clockwise.
4. This procedure may be repeated periodically or when needed due to lowered filtering performance or water flow.

NEW CARTRIDGE REPLACEMENT:

According to individual water conditions, the **#W5424 REF Chlorgon Replacement Cartridge** should be replaced after 6-18 months of service by performing the following procedure.

1. Open the filter housing by unscrewing the two Filter Halves counter-clockwise.
2. Remove and replace the used filter with the new Chlorgon Cartridge. Check that the O-Ring located inside each of the Filter Housing Halves is properly seated on the O-Ring Channel. *(NOTE: A small amount of Vaseline applied in the O-Ring Channel will hold the O-Ring in place.)*
3. Close the filter housing by screwing the Filter Halves clockwise.

Protect your Chlorgon: Do not leave your system under constant pressure that can build up. Turn off the faucet to relieve pressure from the system. Also, secure your garden hose so it does not stress the Chlorgon housing when the hose is moved or pulled.